



Cable Specification

C07-B200201P/WH – BT2002 Type 75ohm Coaxial Cable
Cable for use as interconnection between transmission equipment or digital telephone systems.

Unit 2 Eldon Road
Industrial Estate,
Beeston,
Nottingham,
NG9 6DZ

0115 968 3540
sales@ksm.co.uk
www.ksm.co.uk



Image is for reference only. ©KSM Ltd

Construction

Conductor

Material: Bare Copper
Construction: 7/0.20mm

Dielectric

Material: Polyethylene
Diameter: 2.40mm

1st Braid Screen

Material: Bare Copper
Coverage: 94%

2nd Braid Screen

Material: Bare Copper
Coverage: 95%

Sheath

Material: Polyvinyl Chloride
Diameter: 5.10mm

Mechanical Characteristics

Operating Temperature (°C): -15 to +70
Min. Installation Temperature (°C): -5

Electrical Characteristics at 20°C

Characteristic Impedance (Ω):	75±3
Inner Conductor DC Resistance (Ω/km):	≤89
Capacitance (pF/m):	53±3
Velocity Ratio (%):	83
Attenuation (dB/100m):	5MHz <4.0
	100MHz <17.3
	200MHz <23.0
	500MHz <41.0

Compliance

RoHS II Directive (2011/65/ EU & 2015/863)
REACH (1907/2006)

Part Options

C07-B200201P/WH | BT2002 Type White PVC

Connectors, cable preparation tools and crimp tools are also available.

Important:

All information, including illustrations, are correct at time of publishing. Users however should independently evaluate the suitability of each product for their particular application. KSM Ltd makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Specifications are subject to change without notice. In addition KSM Ltd reserves the right to make changes, without notification to the Buyer, to processing or materials that do not affect compliance with any applicable specification. All values are given as a nominal representation. Copying of this information in whole or part must be authorised in writing by KSM Ltd and the information must only be used for the purposes authorised. ©KSM Ltd.