



Cable Specification

C07-R179S01L/BK – RG179 Type 75ohm Solid Coaxial Cable LSF
Cable for use with video signal transmissions, CCTV and Audio/Visual applications.

Unit 2 Eldon Road
Industrial Estate,
Beeston,
Nottingham,
NG9 6DZ

0115 968 3540
sales@ksm.co.uk
www.ksm.co.uk



Image is for reference only. ©KSM Ltd

Construction

Conductor

Material: Tinned Copper
Construction: 1/0.36mm

Dielectric

Material: Foam Polyethylene
Diameter: 1.65mm

Braid Screen

Material: Tinned Copper
Construction: 0.10mm x 16 x 6 (95%)

Sheath

Material: Low Smoke and Fume
Diameter: 2.55mm

Electrical Characteristics at 20°C

Characteristic Impedance (Ω):	75 $\pm$ 3
Max. Conductor DC Resistance (Ω /km):	190
Min. Insulation DC Resistance ($M\Omega$ */km):	>100
Capacitance (pF/m):	54
Velocity Ratio (%):	82
Rated Voltage (V):	30
Attenuation (dB/100m):	10MHz 6.00
	100MHz 19.50
	200MHz 28.00

Compliance

RoHS II Directive (2011/65/EU & 2015/863)
REACH (1907/2006)

Part Options

C07-R179S01L/BK | RG179 Type Solid Black LSF

LSZH sheath and other colour options available on request.

Connectors, cable preparation tools and crimp tools are also available.

Important:

All information, including illustrations, are correct at time of publishing. Users however should independently evaluate the suitability of each product for their particular application. KSM Ltd makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Specifications are subject to change without notice. In addition KSM Ltd reserves the right to make changes, without notification to the Buyer, to processing or materials that do not affect compliance with any applicable specification. All values are given as a nominal representation. Copying of this information in whole or part must be authorised in writing by KSM Ltd and the information must only be used for the purposes authorised. ©KSM Ltd.