



Unit 2 Eldon Road
Industrial Estate,
Beeston,
Nottingham,
NG9 6DZ

0115 968 3540
sales@ksm.co.uk
www.ksm.co.uk

Cable Specification

C07-R223Z01P/BK – RG223 Type 50ohm Coaxial Cable PVC
Cable for use with RF transmissions, radio systems, test cable sets and GPS applications.



Image is for reference only. ©KSM Ltd

Construction

Conductor

Material: Silver Plated Copper
Construction: 1/0.90mm

Dielectric

Material: Solid Polyethylene
Diameter: 2.95mm

1st Braid Screen

Material: Silver Plated Copper
Construction: 0.127mm x 16 x 7 (96%)

2nd Braid Screen

Material: Silver Plated Copper
Construction: 0.127mm x 16 x 7 (95%)

Sheath

Material: Polyvinyl Chloride
Diameter: 5.40mm

Mechanical Characteristics

Operating Temperature (°C): -15 to +70

Electrical Characteristics at 20°C

Impedance (Ω):	50±3
Max. Conductor DC Resistance (Ω/km):	30
Capacitance (pF/m):	101
Velocity Ratio (%):	66
Attenuation (dB/100m):	100MHz 15.8
	200MHz 23.0
	300MHz 28.2
	500MHz 36.8
	800MHz 48.5
	1000MHz 54.1

Compliance

RoHS II Directive (2011/65/EU & 2015/863)
REACH (1907/2006)

Part Options

C07-R223Z01P/BK | RG223 Type Black PVC

LSZH and Mil-Spec options available on request.

Connectors, cable preparation tools and crimp tools are also available.

Important:

All information, including illustrations, are correct at time of publishing. Users however should independently evaluate the suitability of each product for their particular application. KSM Ltd makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Specifications are subject to change without notice. In addition KSM Ltd reserves the right to make changes, without notification to the Buyer, to processing or materials that do not affect compliance with any applicable specification. All values are given as a nominal representation. Copying of this information in whole or part must be authorised in writing by KSM Ltd and the information must only be used for the purposes authorised. ©KSM Ltd.