



Unit 2 Eldon Road
Industrial Estate,
Beeston,
Nottingham,
NG9 6DZ

0115 968 3540
sales@ksm.co.uk
www.ksm.co.uk

Cable Specification

C07-R400M01F/BN – RG400/U Mil Spec 50ohm Coaxial Cable FEP
Cable generally to MIL-C-17 for use with wireless, broadcast, and radio frequency transmission applications.



Image is for reference only. ©KSM Ltd

Construction

Conductor

Material: Silver Plated Copper
Construction: 19/0.20mm

Dielectric

Material: Solid Polytetrafluoroethylene
Diameter: 2.95mm

1st Braid Screen

Material: Silver Plated Copper
Coverage: 95%

2nd Braid Screen

Material: Silver Plated Copper
Coverage: 94%

Sheath

Material: Fluorinated Ethylene
Propylene
Diameter: 4.95mm

Mechanical Characteristics

Operating Temperature (°C): -55 to +200

Electrical Characteristics at 20°C

Characteristic Impedance (Ω):	50±2
Capacitance (pF/m):	105
Velocity Ratio (%):	70
Voltage (V):	1900
Attenuation (dB/100m):	
100MHz	14.4
400MHz	31.4
1000MHz	48.2
3000MHz	88.4

Compliance

RoHS II Directive (2011/65/EU & 2015/863)
REACH (1907/2006)

Part Options

C07-R400M01F/BN | RG400/U Mil Spec Brown FEP

Connectors, cable preparation tools and crimp tools are also available.

Important:

All information, including illustrations, are correct at time of publishing. Users however should independently evaluate the suitability of each product for their particular application. KSM Ltd makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Specifications are subject to change without notice. In addition KSM Ltd reserves the right to make changes, without notification to the Buyer, to processing or materials that do not affect compliance with any applicable specification. All values are given as a nominal representation. Copying of this information in whole or part must be authorised in writing by KSM Ltd and the information must only be used for the purposes authorised. ©KSM Ltd.