



Unit 2 Eldon Road
Industrial Estate,
Beeston,
Nottingham,
NG9 6DZ

0115 968 3540
sales@ksm.co.uk
www.ksm.co.uk

Cable Specification

C15-4x22NP/BK – 2 Core 100V Line Speaker Cable Black PVC
Heavy duty 2 core speaker cable suitable for 100V line PA speaker installations.



Image is for reference only. ©KSM Ltd

Construction

Conductor

Material: Copper/Copper Clad Aluminium

Construction:	Cu Strands	CCA Strands
45/0.18mm	25 x 0.18mm	20 x 0.18mm
79/0.18mm	40 x 0.18mm	39 x 0.18mm

Insulation

Material: Polyvinyl Chloride

Diameter: 45/0.18mm 2.50mm
79/0.18mm 2.80mm

Colour Code: Red, Black

Sheath

Material: Polyvinyl Chloride

Diameter: 45/0.18mm 7.80mm
79/0.18mm 8.80mm

Compliance

RoHS II Directive (2011/65/EU & 2015/863)
REACH (1907/2006)

Part Options

C15-4U22NP/BK	2 Core 45/0.18mm 100V Line
C15-4922NP/BK	2 Core 79/0.18mm 100V Line

Important:

All information, including illustrations, are correct at time of publishing. Users however should independently evaluate the suitability of each product for their particular application. KSM Ltd makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Specifications are subject to change without notice. In addition KSM Ltd reserves the right to make changes, without notification to the Buyer, to processing or materials that do not affect compliance with any applicable specification. All values are given as a nominal representation. Copying of this information in whole or part must be authorised in writing by KSM Ltd and the information must only be used for the purposes authorised. ©KSM Ltd.