

## Product Specification

### F05-31xxxx/xx – Polyester Braid Sleeving

Expandable sleeving for management and bundling of cables and hoses.



Image is for reference only. ©ksm Ltd

### Construction

| Material:     | Polyester |      |
|---------------|-----------|------|
| Nominal Size: | Min.      | Max. |
| 3mm           | 1mm       | 6mm  |
| 4mm           | 2mm       | 7mm  |
| 5mm           | 3mm       | 8mm  |
| 6mm           | 3mm       | 9mm  |
| 8mm           | 5mm       | 16mm |
| 10mm          | 7mm       | 19mm |
| 12mm          | 8mm       | 24mm |
| 15mm          | 10mm      | 27mm |
| 20mm          | 14mm      | 30mm |
| 25mm          | 18mm      | 35mm |
| 30mm          | 20mm      | 50mm |
| 40mm          | 30mm      | 60mm |
| 50mm          | 40mm      | 80mm |

### Mechanical Characteristics

|                             |              |
|-----------------------------|--------------|
| Operating Temperature (°C): | -50 to + 150 |
| Melt Point (°C):            | 240 ±10      |

### Compliance

RoHS II Directive (2011/65/EU & 2015/863)  
REACH (1907/2006)

### Part Options

|               |                     |
|---------------|---------------------|
| F05-310030/** | Braid Sleeving 3mm  |
| F05-310040/** | Braid Sleeving 4mm  |
| F05-310050/** | Braid Sleeving 5mm  |
| F05-310060/** | Braid Sleeving 6mm  |
| F05-310080/** | Braid Sleeving 8mm  |
| F05-310100/** | Braid Sleeving 10mm |
| F05-310120/** | Braid Sleeving 12mm |
| F05-310150/** | Braid Sleeving 15mm |
| F05-310200/** | Braid Sleeving 20mm |
| F05-310250/** | Braid Sleeving 25mm |
| F05-310300/** | Braid Sleeving 30mm |
| F05-310400/** | Braid Sleeving 40mm |
| F05-310500/** | Braid Sleeving 50mm |

\*\* = BK for Black, GY for Grey. Other colours available on request.

Please note due to manufacturer variations reel sizes available may differ from those stated.

#### Important:

All information, including illustrations, are correct at time of publishing. Users however should independently evaluate the suitability of each product for their particular application. KSM Limited makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Specifications are subject to change without notice. In addition KSM Limited reserves the right to make changes, without notification to the Buyer, to processing or materials that do not affect compliance with any applicable specification. All values are given as a nominal representation. Copying of this information in whole or part must be authorised in writing by KSM Ltd and the information must only be used for the purposes authorised. ©ksm Ltd.